

MODELS	T5.110 AUTO COMMAND	T5.120 AUTO COMMAND	T5.130 AUTO COMMAND	T5.140 AUTO COMMAND
New Holland engine*	NEF			
No. of cylinders / Capacity / Valves / Compliant emissions regulations	4 / 4485 / 4 / Stage V			
ECObLue™ SCR HI-eSCR 2 system (Selective Catalytic Reduction)	●	●	●	●
Max. horsepower - ISO TR14396- ECE R120 [kW/hp(CV)]	83 / 110	91 / 120	98 / 130	105 / 140
Rated horsepower (Rated speed @2200rpm) - ISO TR14396- ECE R120 [kW/hp(CV)]	74 / 100	81 / 110	88 / 120	96 / 130
Max. torque - ISO TR14396 [Nm]	520 @ 1300rpm	551 @ 1300rpm	610 @ 1300rpm	630 @ 1300rpm
Diesel tank capacity standard / AdBlue tank capacity (Litres)	180 / 19			
Electrical 12 volt alternator Standard / Optional (Amps)	120 / 200			
Auto Command™ Continuously Variable Transmission (40kph or 40 ECO)	●	●	●	●
Min. speed / Max. speed [kph]	0,02 / 40 @ 1550rpm			
Auto Command™ electronic park brake	●	●	●	●
Active StopStart function	●	●	●	●
Force base propulsion control	●	●	●	●
Standard Front Axle (Class 1.5 HD)	●	●	●	●
Optional Front axle (Class 1.75)	○	○	○	○
Terraglide™ front axle suspension	○	○	○	○
Terralock™ functions (Auto Diff / Auto 4WD)	○	○	○	○
Turning radius with 4WD / Terraglide™ suspended front axle (mm)	4963			
PTO engine speed at: 540 / 1000 [rpm]	1938 / 1926			
PTO engine speed at: 540 / 540E / 1000 [rpm]	1969 / 1546 / 1893			
PTO engine speed at: 540E / 1000 / 1000E [rpm]	1546 / 1893 / 1621			
Ground Speed PTO	○	○	○	○
Auto PTO management	●	●	●	●
Front PTO (1000rpm)	○	○	○	○
Standard Hydraulic Main Pump flow / Pump pressure [Lpm/Bar]	82 / 200			
Optional MegaFlow™ Hydraulic Main Pump flow / Pump pressure [Lpm/Bar]	108 / 200			
Standard Steering and services pump flow [Lpm/Bar]	34.3 / 230			
Max. no. Deluxe rear valves with diverter fitted	4			
Max. no. mid mount valves	3			
Mid mount Electronic joystick control	○	○	○	○
Electronic Draft Control (EDC)	●	●	●	●
Max. lift capacity at ball ends [kN]	5500			
Front linkage lift capacity at ball ends (through the range) [kN]	2250			
Four pillar 360° Horizon™ cab with FOPS - OECD Code 10 Level 1	●	●	●	●
Low profile roof	○	○	○	○
High visibility roof hatch	○	○	○	○
Comfort Ride™ cab suspension	○	○	○	○
Automatic climate control	○	○	○	○
Comfort seat with seat belt	●	●	●	●
Dynamic Comfort™ / Auto Comfort™ Active Climate Control heated seat with seat belt	○ / ○	○ / ○	○ / ○	○ / ○
Instructors seat with seat belt	○	○	○	○
Luxury Pack (Leather Steering wheel and carpet)	○	○	○	○
Blue Power Pack	-	-	-	○
4 halogen lighting pack	●	●	●	●
8 /12 /16 LED lighting pack	○ / ○ / ○	○ / ○ / ○	○ / ○ / ○	○ / ○ / ○
IntelliView™ IV colour monitor with ISO 11783 connector	●	●	●	●
ISOBUS Class III (External and in cab connection)	○	○	○	○
Headland Turn Sequencing II (HTS II)	○	○	○	○
PLM® Connect telematics	○	○	○	○
Dimensions on rear tyres^(A)	540/65R34	540/65R38	16.9R38	600/65R38^(B)
Max. overall length inc. weight carrier to rear linkage (mm)	4170			
Min. width (mm)	1888 [Optional Narrow Fender]	2288 [Standard fender]	1888 [Optional Narrow Fender]	2288 [Standard fender]
Overall height of low profile cab (mm)	2695		2755	2780
Wheelbase (mm)	2490			
Minimum shipping weights (kg)	5500			
Max. permissible weight (kg)	8800			

● Standard ○ Optional - Not available * Developed by FPT Industrial ** Biodiesel blend must fully comply with the latest fuel specification EN14214:2009 and operation is in accordance with operator manual guidelines
(A) Rear tyres other than those mentioned are available: 16.9R38, 480/70R38, 540/65/R34, 540/65R38, 600/65R38 (B) Only compatible with Comfort Ride™ cab suspension.



www.newholland.com



The data indicated in this folder are approximate. The models described here can be subjected to modifications without any notice by the manufacturer. The drawings and photos may refer to equipment that is either optional or intended for other countries. Please apply to our Sales Network for any further information. Published by New Holland Brand Communications. Bts Adv. - Printed in Italy - 10/18 - (Turin) - 180016/INT